





Stepless Speed Control, Large Air Flow, Power Saving

- Suitable for indoor and outdoor sultry areas. Such as factories, garage, warehouse, restaurants, etc.
- 2. Evaporative cooling with no mists. Effectively filters dust and lower the temperature.
- 3. Save electricity in an air conditioned space. Cool the room faster, then lessen the power consumption of the AC system.
- 4. Easy to clean and maintain. Wash the cooling pads and change the water inside the tank regularly can keep it clean.
- Connect the water inlet to a faucet with the hose we provide, the tank will fill automatically. Add some ice cube into the tank can enhance the cooling effect.













Wheels
For Portable Use

Portable Use







MT-M602-COOL



MT-M702-COOL





■ MT-M802-COOL







Product Details (For DC series data, please contact us.)

Model	MT-M502-COOL	MT-M602-COOL	MT-M702-COOL	MT-M703-COOL	MT-M802-COOL	MT-M902-COOL
External Frame	PE	PE	PE	PE	PE	PE
Blades	50" 3 SMC Blades	42" 6 Nylon 6 + Fiber Blades	30" 3 Nylon 6 + Fiber Blades	30" 3 Nylon 6 + Fiber Blades	24" 3 Nylon 6 + Fiber Blades	18" 3 Nylon 6 + Fiber Blades
Motor	2HP Grade F	1.5HP Grade F	1/2HP Grade F	1/2HP Grade F	1/2HP Grade F	1/3HP Grade F
Pole	10 Pole	10 Pole	6 Pole	6 Pole	6 Pole	4 Pole
Rotating Speed (Max.)	640RPM	580RPM	1000RPM	1100RPM	1100RPM	1380RPM
Sound Volume (Max.)	75dB	70dB	65dB	60dB	55dB	55dB
Voltage	1 ∮ 220V, 60Hz	1 \$ 220V, 60Hz	1 ∮ 110V, 60Hz	1 ∮ 110V, 60Hz	1 ∮ 110V, 60Hz	1 ∮ 110V, 60Hz
Wind Fetch (Max.)	30m up	25m up	20m up	20m up	15m up	15m up
Size	L180xW88xH220 cm	L155xW81xH186 cm	L126xW72xH160 cm	L132xW69xH172 cm	L98xW70xH141 cm	L75xW50xH130 cm
Water Storage	230L	180L	145L	170L	120L	60L
Weight	160kg	120kg	90kg	100kg	75kg	45kg
Total Weight with Water	390kg	300kg	235kg	270kg	195kg	105kg